



WD2-6A

Approval		
Electrical		
Standard	UL	IEC
Rated voltage	600V	500V
Rated current	10A	10A
Wire size	24-10AWG	0.2-6.0mm ²
T/W/End plate	13/62/2.5mm	
Height(NS35:7.5/NS35:15)	61.5/69mm	
Rated surge voltage/contamination class	6KV/3	
Stripping length	13mm	
Insulating material/Inflammability class	PAV-0	

HOW TO ORDER :

	-		P	-	1	-	X X X Customer Request																		
Series No.		No. of pole			Color																				
					<table border="1"> <tr> <td>1</td><td>Gray</td> <td>4</td><td>Green</td> <td>7</td><td>Transp-arent</td> </tr> <tr> <td>2</td><td>Blue</td> <td>5</td><td>Orange</td> <td>8</td><td>Yellow</td> </tr> <tr> <td>3</td><td>Black</td> <td>6</td><td>Red</td> <td>9</td><td>white</td> </tr> </table>	1	Gray	4	Green	7	Transp-arent	2	Blue	5	Orange	8	Yellow	3	Black	6	Red	9	white		
1	Gray	4	Green	7	Transp-arent																				
2	Blue	5	Orange	8	Yellow																				
3	Black	6	Red	9	white																				