



公差/General tolerances(mm)													0.1/1.0
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	±2°
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

额定电压/电涌/Rated Voltage(V)/Current(A)	300/17.5	4	4	4
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4	4
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4/24~12	176*56*38	9~11	-40~+105
尺寸/Size(mm)	176*56*38	9~11	-40~+105	Yes
剥线长度/Stripping length(mm)	9~11	-40~+105	Yes	
使用温度范围/Operating temperature(°C)	-40~+105	Yes		
符合RoHS环保要求/Conform to RoHS	Yes			

MATERIAL:	/	SURFACE:	
MAT NO.:	/		
STATUS:	/		
APPD:lan ChH	2023.12.14	NAME:	KVMK4-1-25
CHKD:Yu JZh	2023.12.14		
DFT:CENGMZ_2023.12.14		DRAWING NO.:	KVMK4-1-25
		TYPE:	CUSTOMER_DRAWING
		SCALE:	2:1
		SHEET:	1/1

 康伟电子有限公司
KANGWEI ELECTRONICS CO., LTD